## **Specification Sheet**

## HDS 745-4 M Eco (110/240V)

# A medium class Hot Water High-Pressure Cleaner.

The HDS 745-4 M Eco is a medium class 4 pole machine that combines innovative engineering with user convenience, economy and a long service life even under demanding cleaning conditions. It is packed with features such as the rear control panel that enables all the indicators to be read easily, Easy press trigger gun, high performance burner with low emissions and the soft dampening system (SDS) that reduces vibrations thus extending the life of the machine. Ideal for businesses needing to remove grease or heavy dirt.

- 4 pole, water cooled electric motor.
- 3 piston axial pump with ceramic pistons.
- LED indicators show the status of the most important machine functions.
- Pivoting 1050mm stainless steel spray lance.
- Tanks for detergent, scale inhibitor and fuel can be filled from outside.
- Easy press trigger gun can be held and used with greatly reduced effort.
- Low fuel cut-out facility.
- Motor protection switch to protect against overload.
- Flue gas temperature limiter switches off the drive motor if the flue gas exceeds 300°C.



TEL: 01295 752 082



#### Technical data HDS 745-4 M Eco (110v) HDS 745-4 M Eco (240v)

Power supply	(~/V/Hz)	1/110/50	1/240/50
Water flow rate	(l/h)	350-700	350-700
Pressure	(mbar/MPa)	30-90	30-90/3-9
Max. temperature	(°C)	140/80	155/80
Connected load	(kW)	3.2	3.2
Consumption, fuel oil	(kg/h)	4.3	4.3
Fuel/Detergent tank	(I)	25/20	25/20
Weight	(kg)	130	130
Dimensions (L x W x H)	(mm)	1285 x 690 x 835	1285 x 690 x 835
Order no.		1.026-346	1.026-345

#### **Target Markets**

- Construction
- Hire/Fleet
- Automotive
- Trade
- Agriculture



#### **Standard Accessories**

- Easy press trigger gun
- 10m High-Pressure hose
- 1050mm Spray lance
- Power nozzle
- SDS system

### **Optional Accessories**

• 10m High-Pressure extension hose	(6.389-891)
Coupling (for above)	(4.403-002)
<ul> <li>Rotary wash brush</li> </ul>	(4.762-284)
Dirtblaster	(4.763-252)
FR 30 Hard surface cleaner	(2.641-065)
Nozzle (for above)	(2.640-401)



